



#17-14 ZAC Tapper Fastener

Designed for replacement of Stitch / Panel overlap fasteners into metal or wood substrates.

Features:

- #17 diameter for direct replacement of #12 or #14 (1/4-14) stitch/lap screws.
- Lifetime limited warranty / guarantee against red rust corrosion on the head of this ZAC fastener
- Extra thick EPDM sealing washer for improved seal.

No predrill required for panels up to 24 ga, No predrill required for wood applications,

Predrill required for applications into red iron or steel purlins.

Specifications

3/8" Hex Drive, AB TH/Point

- Torsional: 180 in-lbs
- Tensile: 5300 lbs. min.
- Shear: 3200 lbs min.
- Pull out 12ga metal 1716 lbs ult
- Pull out 24ga metal 261 lbs ult
- Pull out 26ga metal 225 lbs ult
- Pull out 3/4" Plywood 497 lbs avg
- Pull out 1/2" Plywood 292 lbs avg
- Pull out 5/8" OSB 413 lbs avg
- Pull out 15/32" OSB 178 lbs avg
- Pull out 2" x 4" SYP 598 lbs avg
- Thread Diameter: Maj: 0.295" Min: 0.214"

Selection

Sizes	Qty/Box	Part#	Head Style
#17 x 1"	1,500	DMI2A6045LFF	3/8 AFH
#17 x 1-1/2"	1,000	DMI2A6066LFF	3/8 AFH

Please note this fasteners is bagged in a standard 250 count.

Installation

3/8" Hex driver required. DMI suggests LSC drivers.
 0-2500 rpm electric screw gun with depth sensing nose piece or torque control device.
 Suggested drill speed into most substrates is 1800 rpm.
 Do not overdrive or under drive, not suggested for use with impact driver installation tools.

Approximated values are average ultimate values.
 Values may change with strength and condition of substrate metal or wood.

Limitations: Not recommended for pressure treated wood substrates. Not recommended for aluminum or copper roofing panels. Not recommend for installation by impact drivers. Contact DMI for MSDS information
 All sizes and color combinations may not be available for immediate shipment from all service centers.

To find a distributor call 855-800-8878 or visit www.directmetalsinc.com